

CLAIMS

What is claimed is:

1. A method for entering system firmware recovery mode for use with a computer system computer system having one or more buttons and a flash memory, the method comprising the steps of:

5 detecting status of one or more software-detectable buttons at power-on of the computer system;

distinguishing between normal use of the one or more software-detectable buttons and as firmware recovery buttons; and
initiating system firmware recovery mode.

2. The method recited in Claim 1 wherein the one or more software-detectable buttons comprise power and/or sleep buttons.

3. The method recited in Claim 1 wherein the detecting step comprises reading a predetermined device register.

4. The method recited in Claim 3 wherein the predetermined device register comprises a PM1a_CNT register.

5. The method recited in Claim 3 wherein the predetermined device register comprises a PWR-LVL register.

6. The method recited in Claim 2 wherein the distinguishing step comprises holding down both the power button and the sleep button at power-on.

7. The method recited in Claim 2 wherein the distinguishing step comprises:
selectively holding down the power or sleep button at power-on for a predetermined time period; and
providing an indication to release the selected button.

8. The method recited in Claim 1 wherein the distinguishing step comprises holding down a platform-specific button instead of or in combination with power and sleep buttons at power-on.

9. The method recited in Claim 1 wherein the computer system further comprises a disk drive and wherein the initiating step comprises reprogramming the flash memory using the disk drive.

10. The method recited in Claim 1 wherein the computer system further comprises an input/output port and wherein the initiating step comprises reprogramming the flash memory using the input/output port.

11. The method recited in Claim 1 wherein the computer system further comprises a disk drive and an input/output port and wherein the initiating step comprises reprogramming the flash memory using both the a disk drive and the input/output port.

12. The method recited in Claim 1 wherein the distinguishing step comprises simultaneously holding down the one or more software-detectable buttons.

13. The method recited in Claim 1 wherein the distinguishing step comprises holding down the one or more software-detectable buttons in a predetermined sequence.

"05210" 49844669